ProLite H511S-B | 20.1"

The 20.1” ProLite H511S offers plenty of area to display every element of even the most space-hungry applications. The IPS LCD technology provides a native resolution of 1600 x 1200 and a lateral viewing angle of 176°. The height of the display can be adjusted through 110mm and the screen itself rotates for a landscape or portrait viewing mode. Flexible inputs (1 x VGA & 1 x DVI-D with cables included) reinforces the position of the ProLite H511S as the professional 20.1” LCD of choice. Available in both ivory and black

Technical data	
Panel	IPS
Diagonal	20,1“ (51 cm)
Display area h x w	306 x 408 mm
Response time	16 msec
Contrast ratio	400 : 1 typical
Brightness	250 cd / m² typical
Viewing zone	horizontal/vertical: 176°/176°; right/left: 88°/88°, up/down: 88°/88°
Display colour	16,77 Million
Pixel pitch h x v	0,255 x 0,255 mm
Horizontal sync	31-80 (digital input), 24-80 (analog input) KHz
Vertical sync	56 - 85 Hz
Bandwith	162 MHz
Native resolution	1.9 MegaPixel (1600 x 1200)
Input connector	DVI-D, D-Sub mini 15 pin
Speaker	2 x 2 W (Stereo)
Included accessories	Power Cable, D-Sub Cable, audio cable, user manual, Pivot® & Liquid view software
Optional accessories	Screen protection sheet
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers
Controls	On-Screen-Display in 6 languages (D, GB, F, ES, Jp, I) and 7 Front controls (Power, Auto-Setup, Exit/Volume, Brightness, Contrast, Menu, Input)
User controls	brightness, contrast, colour temperature, sRGB, auto set-up, Eco mode, horizontal / vertical position, clock, phase, sharpness, gamma correction, Eco mode, OSD position, OSD language, zoom, screen rotation (Portait mode), reset, signal selection, volume
Driver	Windows 95 / 98 / 2000 / ME / XP
Ergonomics	TCO'03 (ProLite H511S-B: TCO'99), MPR III (prEN50279), ISO 13406-2
Safety	CE, TÜV GS, FCC-B, UL/C-UL, VCCI-B, CCC
Power supply	AC 100 - 240 V, 50 / 60 Hz
power supply	internal
Power usage	max. 85 W in normal use, max. 5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington®-lock
VESA mounting	100 mm
Height adjustment	110 mm
Rotation (pivot function)	90°
Swivel Stand	70°, each 35° right and left
Tilt angle	35° up, 5° down
Weight	10,0 with stand kg
Dimensions w x h x d	446 x 391,5 x 242; 446 x 375 x 70 without stand mm

All trademarks and registered trademarks acknowledged. E & O E. Specifications subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defaults.

Megapixel describes the size of your desktop and therefore the amount of information your display can show. A lcd with a physical resolution of 9.2 mega pixels (3840 x 2400) can show 6 times more information than a display with 1.3 mega pixels (1280 x 1024). That means your desktop is about 600 percent bigger.